

PRECISE, RELIABLE AND VERSATILE FLUID HANDLING

For measurement of the PH, Redox / ORP value



ACCURATE AND RELIABLE

The Emaux "CyberSync" Peristaltic Dosing Pump series is indeed a groundbreaking addition to pool maintenance technology. Designed for swimming pools ranging from 30m² to 150m², it offers three versions: Core-Pro, Core-Plus, and Core, with five different models to cater to various needs. Utilizing peristaltic technology, these pumps ensure precise and reliable dosing, keeping pools balanced and sanitized. The user-friendly control panel, chemical-resistant BTP tube, and durable shield enhance its dependability. Additionally, its wide voltage range (110V to 240V) simplifies installation across different electrical systems, making it an excellent choice for maintaining a crystal-clear pool.



Technical Overview:

Chemical Concentration: Liquid Chlorine up to 30% Muriatic acid up to 40% Sulfuric acid up to 40%

Operating Voltage:	110-240V 50/60Hz
Max Dosing Rate:	3 L/hour
Consumption:	20 watt
Pressure:	1.5 bar [22 psi]
Strainer / injector Tube Size:	4 x 6 (mm) tube

Core-Pro Version











The Emaux CyberSync Core-Pro is an advanced peristaltic dosing pump designed for seamless automatic dosing. It integrates with Emaux pH or ORP probes, ensuring precise and comprehensive dosing automation. Additionally, it supports external connectivity for pump control, level probes, alarms, and other dosing pumps, offering a straightforward and complete automation solution for various dosing requirements. This makes it an excellent choice for maintaining optimal water quality with minimal manual intervention.

Model:	DP300-X	
Display:	LED (Dot Matrix)	
Depoly Probe:	ORP or pH	

External connection*: Pump, Alarm, Level sensor

*Max power for external dosing pump: 50w

Code	Model	Pressure bar [psi]	Max dosing rate L/hour Measurable range Operating vol		Operating voltage v	Input power W
9130113	DP300-X-ORP	1.5 [22]	3	ORP: 300 to 900mV	110-240	20
9130117	DP300-X-PH	1.5 [22]	3	pH4 - pH10	110-240	20







Model: DP300

Display: LED

The Emaux CyberSync Core is indeed a versatile dosing solution designed for ease of use. It allows users to effortlessly adjust the dosing rate, ensuring precise control over chemical levels.

Code	Model	Pressure bar [psi]	Max dosing rate L/hour		
9130116	DP300	1.5 [22]	3	110-240	20

Core-Plus Version

The Emaux CyberSync Core-Plus is a fantastic solution for maintaining optimal pool chemistry! Its automatic dosing feature for ORP and pH control, along with the user-friendly LED display, makes it easy to monitor and adjust water quality in real-time. Whether you choose the ORP or pH version, this device ensures that your pool remains in perfect balance, providing a hassle-free experience for pool owners.





Display: LED

Probe: ORP



Model: DP300-PH


Display: LED

Probe: pH


PH Q


Code	Model	Pressure bar [psi]	Max dosing rate L/hour	Measurable range	Operating voltage v	Input power W	
9130114	DP300-ORP	1.5 [22]	3	ORP: 300 to 900mV	110-240	20	
9130115	DP300-PH	1.5 [22]	3	pH4 - pH10	110-240	20	

Product Dimensions









Probe and Accessories Specifications

Code	Product Name	Parameter	Photo	DP300-X-ORP	DP300-X-PH	DP300-ORP	DP300-PH	DP300
50932002	ORP probe	Pressure: 7 bar Material: epoxy Measuring range: -300 to 900mV (with 3m signal line) Electrode diametaer: 12mm		\checkmark	⟨x ⟩	\triangleleft	⟨x ⟩	X
50932002	pH probe	Pressure: 7 bar Material: epoxy Measuring range: 0- 14 (with 3M signal line) Electrode body diametaer: 12mm		X	\triangleleft	*	⊘	X
50932004	Probe holder	½" male thread					\checkmark	$\langle \mathbf{x} \rangle$
51301007	256 buffer solution	256mV, 30mL	5	\bigcirc	$\langle \mathbf{X} \rangle$	\bigcirc	$\langle \mathbf{X} \rangle$	$\langle \mathbf{x} \rangle$
51301011	pH probe buffer solution pH4 and pH7	pH 4.0 and pH 7.0, 30mL	+	X	\bigcirc	X	⊘	X
41501023	Dosing pipe fitting	Pressure: 7 bar PE Tube: 4x6 tube x 1 pc PVC Tube: 4x6 tube x 1 pc PVDF Injector: ½" meal thread x 1 pc PVDF strainer: with valve x 1 pc	lge-	Ø	⊘	%	Ø	Ø
50903036	Level probe	With 2m signal line	100	\checkmark	Ø	⟨x ⟩	X	X
11303006	Wall mount holder	With screw		\bigcirc	\bigcirc	\checkmark	\checkmark	⊘
534280	25L Dosing tank (Optional item)	Size: 320 X 200 X 390mm		X >	⟨x ⟩	⟨x ⟩	⟨x ⟩	X

CyberSyncy

PRECISE, RELIABLE AND VERSATILE FLUID HANDLING

FOR MEASUREMENT OF THE PH, REDOX / ORP VALUE



Core Version





Product features:

- Easy installation and maintenance
- User-friendly interface and operation
- Precise and reliable pool chemical control
- Versatile model option
- Adjustable flow rate control





EMAUX WATER TECHNOLOGY CO., LTD

ADDRESS: 2/F, Lockhart Centre, No. 301-307 Lockhart Road,

Wanchai, Hong Kong PHONE +852 2832 9880 www.emauxgroup.com

YOUR PREMIER SUPPLIER

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE © EMAUX WATER TECHNOLOGY CO., LTD. ALL RIGHTS RESERVED.